


SPECIFICATIONS

Metric	British
32.00m	105ft
30.00m	98ft 5in
6.73m	22ft 1in
2.55m	8ft 4in
4.13m	13ft 7in
3.19m	10ft 6in
6.20m×2.45m	20ft 4in×8ft
2.10m	6ft 11in
0.20m	8in
4.86m	15ft 11in
3.80m/6.30m	12ft 6in/20ft 8in
15-625	15-625
	32.00m 30.00m 6.73m 2.55m 4.13m 3.19m 6.20m×2.45m 2.10m 0.20m 4.86m 3.80m/6.30m

Performance		
S.W.L	1000kg	2204lb
S.W.L On Extension	1000kg	2204lb
Max. Occupants	4	4
Gradeability	30%	30%
Travel Speed(Stowed)	3.5km/h	2.17mph
Travel Speed(Raised)	0.3km/h	0.19mph
Max. Working Slope	X-2°/Y-3°	X-2°/Y-3°
Up/Down Speed	160/120sec	160/120sec

Weight			
Overall Weight	23950kg	52800lb	

Power		
Hydraulic Tank	260L	69gal
Lithium Battery	80V/520Ah	80V/520Ah
Charger	80V/80A	80V/80A
Driving Motor	4×56VAC/6kW	4×56VAC/6kW
Lifting Motor	53VAC/28kW	53VAC/28kW







FEATURES

Standard Items

- Proportional Joystick Controls
- Self-Locking Gates
- Automatic One-Way Platform Extension Deck
- Four-Wheel Drive
- Four-Wheel Steering
- Automatic Braking System
- Self-Weight Lowering System
- Tubing Explosion-Proof System
- Onboard Fault Diagnostic System
- Tilt Alarm
- Motion Alarm
- Horn
- Hour Meter
- Charging Protection System
- Flashing LED Beacon
- Foldable Guard Rails
- Drive Enable
- Charging Indicator
- Manual Brake Release
- · Lanyard Attachment Point
- Tie-Down And Lifting Points
- Automatic Leveling Hydraulic Outriggers
- Emergency Pump
- Emergency Stop Button
- Platform Load Sense System
- Drivable At Full Height



ZHEJIANG DINGLI MACHINERY CO., LTD.

Address: No.188 Qihang Road, Deqing, Zhejiang P.R.C 313219

Telephone: +86(572)8681688 E-Mail: export@cndingli.com Https://en.cndingli.com











